

275/K12SF 900RM-1200RM



SHALLOW FOUNDATION REMOVABLE BOLLARD


The removable 275/K12SF bollards have been designed and built for installations with shallow mounted requirements or in presence of underground utilities. The "SF" (shallow foundation) acronym identifies the slimmest laying depth of the entire range.

GENERAL FEATURES

The removable 275/K12SF bollards are used to separate and prevent vehicles from breaching the perimeter of the following areas: Research Centres, Embassies, Police Headquarters, Military Bases, Ministerial Buildings Sites in Sensitive Areas. The product is unique since the system can be composed depending on the project requirements. Starting from a single bollard configuration, the product is adaptable to different needs such as corners, curves and slopes.



Anticorrosion marine treatment




Replaceable stainless steel sleeve painted or brushed

275/K12SF 900RM-1200RM



	275/K12SF-900RM	275/M50SF-1200RM
CYLINDER MATERIAL	S355JR NORMAL STEEL - X5CrNi 18-10 (AISI 304) STAINLESS STEEL - X5CrNiMo 17-12-2 (AISI 316) STAINLESS STEEL	
CYLINDER DIAMETER	271mm	
CYLINDER HEIGHT	900mm	1200mm
CYLINDER THICKNESS	23mm	
CYLINDER NORMAL STEEL FINISH	ANTI-CORROSION TREATMENT - GREY ANTHRACITE STANDARD PAINTING	
CYLINDER STAINLESS STEEL FINISH	GREY ANTHRACITE STANDARD PAINTING OR BRUSHING FULL INOX CYLINDER OR REPLACEABLE SLEEVE	
REFLECTING ADHESIVE STRIP	STANDARD - HEIGHT 55mm	
FOUNDATION DEPTH	200mm (optional: 300mm incl. approx 100mm for finished floor covering, e.g. paving stones)	
IMPACT RESISTANCE (WITHOUT DEFORMATION)	250.000 J	
BREAKOUT RESISTANCE	2.000.000 J	
ANTI-CORROSION TREATMENT "M"	OPTIONAL ORDER IN CASE OF INSTALLATION AT LESS THAN 2KM FROM THE SEA ORDER IN CASE OF INSTALLATION WHERE SALT IS USED ON THE ROAD TO AVOID ICE FOR A PERIOD UP TO 3 MONTHS	
IN COMPLIANCE	PAS68:2013 V/7500(N3)/80 ASTM F2656-07 M50 (K12) IWA 14-1:2013	



PAG.2/3

PILOMAT
HÖRMANN
100% MADE IN ITALY

PILOMAT s.r.l.
www.pilomat.com / pilomat@pilomat.com
Via Zanica 17/p, 24050, Grassobbio (BG) Italy
Tel. +39.035.29.72.20
Copyright 2022© Pilomat S.r.l. All rights reserved

REVIEW 14/07/2022

Information in this document is for reference only. In pursuit of its policy of continuous refinement and improvement, Pilomat reserves the right to amend this information at any time and without prior notice.
Picture shown is for illustration purpose only.

275/K12SF 900RM-1200RM



AVAILABLE ITEMS

BOLLARD 275/K12SF REMOVABLE IN NORMAL STEEL PAINTED equipped with lock including 2 keys

BOLLARD 275/K12SF REMOVABLE IN STAINLESS STEEL PAINTED equipped with lock including 2 keys

BOLLARD 275/K12SF REMOVABLE IN STAINLESS STEEL BRUSHED equipped with lock including 2 keys

SURCHARGE FOR 100mm HIGHER CYLINDER (e.g. for the use of paving stones)

BOLLARD 275/K12SF REMOVABLE WITH REPLACEABLE SLEEVE STAINLESS STEEL PAINTED OR BRUSHED

HEAD WITHOUT LOGO AND REFLECTING STRIP

PAINTING WITH RAL COLOUR ON REQUEST

